



## **TOUCHLESS TECHNOLOGY READER**

iClass® with Keypad



### **Standard Features**

- The AXX-i921 combines a contactless card presentation with a personal identification number (PIN) to support dual authentication of identity. Or, configure the panel for single-factor authentication, using only a card or a PIN.
- All RF data transmission between the card and reader is encrypted using secure algorithms.
- Multi-Layered Security ensures data authenticity and privacy.
- The 12-position weatherproof keypad uses discrete switches to provide positive tactile response, optionally reinforced by an audible tone.
- The keypad also features a waterproof silicone rubber boot, vandal-resistant metal keycaps, and backlit numbering.

## Technical Specifications

**AXX-i921**  
(electrical box size)

Color	Black
Transmit Frequency	13.56 MHz
Mounting	Designed to mount and cover single gang box switch boxes and includes a slotted mounting plate
Power Supply	5-16 VDC; Linear power supplies recommended
Power Supply Requirements	Average: 85 mA Peak: 105 mA
Operating Temp	-31° to 150° F (-35° to 65° C)
Cable Distance	500ft (150m) (22AWG) - use shielded cable for best results
Environmental	IP55
Housing Material	UL94 Polycarbonate
Dimensions (WxHxD)	3.3" x 4.8" x 1.1" (8.4 x 12.2 x 2.8 cm)
Weight	7.7 oz (220g)



Ban-Koe Companies Corporate Headquarters  
9401 James Ave S, Suite 180  
Minneapolis, MN 55431  
(t) 952.888.6688 | (f) 952.888.0304  
[bankoe.com](http://bankoe.com)