

VIDIX CONTROL

Access Control for Every Facility



AXX-PS-7A

CONTROLLER POWER SUPPLY

STANDARD FEATURES

- These units have a wide range of applications for access control, security and CCTV system accessories that require additional power.
- The FACP Interface enables Emergency Egress, Alarm Monitoring, or may be used to trigger other auxiliary devices.

Technical Specifications

AXX-PS-7A

INPUT	115VAC, 60Hz, 1.45 amp
OUTPUT	12VDC or 24VDC selectable output; 6 amp continuous supply current; filtered and electronically regulated outputs; short circuit and thermal overload protection
BATTERY BACKUP	built-in charger for sealed lead acid or gel type batteries; maximum charge current 0.7 amp; zero voltage drop when switching over to battery backup
VISUAL INDICATORS	AC input and DC output LED indicators
OPERATING TEMPERATURE	0° C to 49° ambient
BTU/HR	12VDC: 36.85 BTU/Hr; 24VDC: 73.70 BTU/Hr;
SYSTEM AC INPUT VA REQUIREMENT	166.75VA
PRODUCT WEIGHT	7.8 Lbs (3.538kg)
SHIPPING WEIGHT	8.8 Lbs (3.991kg)
ENCLOSURE	13.5" x 13" x 3.25"